



PIN OUT

NOTE:

- TEST REQUIREMENTS :
  - 100% ELECTRICAL PERFORMANCE TESE
    - Insulation Resistance:DC:200V 10MΩ(MIN).
    - Conductive Resistance:5.0Ω(MAX)
  - applicable equipment:PDA, IPAD, PS3,XBOX, laptop, etc
  - 4K@60hz TV test

NO.	NAME	SPECIFICATION	QTY	UNIT	REMARK
6	PACK	L: xW: xT: mm	1	PCS	
5	TIE	L:8CM-White TIE	2	PCS	
4	PVC	37Pa-White PVC	1	g	
3	PE	LD-PE	1	g	
2	CONN	HDMI 19pin Micro-hdmi/M,Black plastic core, Gold plated terminal, Gold plated iron shell	1	PCS	
		HDMI 19pin A/M,Black plastic core, Gold plated terminal, Gold plated iron shell	1	PCS	
1	WIRE	30AWG(1P×(1/0.25mm BC)+D(1/0.25mmBC))+AL)+5+ 30AWG(1/0.25mmBC)×4C+AL+D(1/0.25mmBC))+Bl 16/5/0.12mmAL-MG)OD:6.0±0.2mm PVC-White L:1000±30mm	1000	mm	

NO.	NAME	HDMI A/M TO Micro HDMI CABLE
CUSTOMER	GRAPHIC	
	UNIT	mm
CHECK	AUDIT	DRAW